



SAFETY DATA SHEET

1. Identification

Product identifier: TERAND GRAFFITI REMOVER

Other means of identification

SDS number: RE1000001319

Recommended restrictions

Product Use: Cleaner

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: CPC
Address: 1000 INTEGRAM DRIVE
PACIFIC, MO 63069
Telephone: 1-800-327-1835
Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Toxic to reproduction Category 2
Aspiration Hazard Category 1

Environmental Hazards

Acute hazards to the aquatic environment Category 3

Label Elements

Hazard Symbol:





Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.
Causes skin irritation.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
May be fatal if swallowed and enters airways.
Harmful to aquatic life.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water/# If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor/# Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Benzene, methyl-	108-88-3	10 - <25%
2-Propanone	67-64-1	5 - <10%
Propane	74-98-6	5 - <10%
Butane	106-97-8	5 - <10%
Ethanol, 2-butoxy-	111-76-2	1 - <5%
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - <5%
Quaternary ammonium compounds, benzyl(hydrogenated tallow	71011-25-1	1 - <5%



alkyl)dimethyl, bis(hydrogenated tallow alkyl)dimethylammonium salt with b		
Sodium hydroxide (Na(OH))	1310-73-2	0.1 - <1%
Morpholine	110-91-8	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

- Ingestion:** Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
- Inhalation:** Move to fresh air.
- Skin Contact:** Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
- Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

- Symptoms:** No data available.
- Hazards:** No data available.

Indication of immediate medical attention and special treatment needed

- Treatment:** No data available.

5. Fire-fighting measures

- General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.
- Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

- Specific hazards arising from the chemical:** Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

- Special firefighting procedures:** No data available.



Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities: Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 2

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Benzene, methyl-	STEL	150 ppm 560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	100 ppm 375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm 375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	300 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	TWA	20 ppm	US. ACGIH Threshold Limit Values (2008)
	TWA	200 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	500 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	STEL	150 ppm 560 mg/m3	US. NIOSH: Pocket Guide to Chemical



			Hazards (2005)
2-Propanone	STEL	1,000 ppm 2,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	1,000 ppm 2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	250 ppm	US. ACGIH Threshold Limit Values (03 2015)
	TWA	750 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	500 ppm	US. ACGIH Threshold Limit Values (03 2015)
	REL	250 ppm 590 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Propane	REL	1,000 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Butane	REL	800 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm 1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Ethanol, 2-butoxy-	TWA	20 ppm	US. ACGIH Threshold Limit Values (2008)
	TWA	25 ppm 120 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	5 ppm 24 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	50 ppm 240 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Ethanol, 2-(2-butoxyethoxy)- - Inhalable fraction and vapor.	TWA	10 ppm	US. ACGIH Threshold Limit Values (03 2013)
Sodium hydroxide (Na(OH))	Ceiling	2 mg/m3	US. ACGIH Threshold Limit Values (2008)
	Ceiling	2 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceil_Time	2 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Morpholine	REL	20 ppm 70 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	30 ppm 105 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	20 ppm	US. ACGIH Threshold Limit Values (2008)
	TWA	20 ppm 70 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	30 ppm 105 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	20 ppm 70 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Quartz (SiO2) - Respirable dust.	REL	0.05 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Quartz (SiO2) - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Quartz (SiO2) - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (2008)
Quartz (SiO2) - Respirable dust.	TWA	0.1 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Quartz (SiO2) - Respirable dust.	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
Quartz (SiO2) - Respirable dust.	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
Quartz (SiO2) - Respirable dust.	OSHA_AC T	0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)



Ethanol, 2-methoxy-	TWA	0.1 ppm		US. ACGIH Threshold Limit Values (2008)
	REL	0.1 ppm	0.3 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	25 ppm	80 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	25 ppm	80 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,2-Ethanediamine	TWA	10 ppm		US. ACGIH Threshold Limit Values (2008)
	REL	10 ppm	25 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 ppm	25 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	10 ppm	25 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Morpholine, 4-ethyl-	REL	5 ppm	23 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	5 ppm	23 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	20 ppm	94 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	5 ppm		US. ACGIH Threshold Limit Values (2008)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL (03 2013)
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL (03 2013)
2-Propanone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEL (03 2015)
Ethanol, 2-butoxy- (Butoxyacetic acid (BAA), with hydrolysis: Sampling time: End of shift.)	200 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethanol, 2-methoxy- (2-Methoxyacetic acid: Sampling time: End of shift at end of work week.)	1 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information:

Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection:

Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection:

No data available.



Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.
Odor:	No data available.
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	-104.44 °C
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	413.682 - 517.1025 hPa (20 °C) 689.47 - 827.364 hPa (50 °C)
Vapor density:	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.



10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix: 17,885.53 mg/kg
Dermal	
Product:	ATEmix: 11,258.7 mg/kg
Inhalation	
Product:	ATEmix: 359.28 mg/l ATEmix : 32.66 mg/l

Repeated dose toxicity	
Product:	No data available.



Specified substance(s):

Benzene, methyl-	LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg (Target Organ(s): Liver, Kidney) Oral Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation): 625 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation - vapor): 2,355 mg/l Inhalation Experimental result, Key study
2-Propanone	NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental result, Key study
Propane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Butane	LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
Ethanol, 2-butoxy-	NOAEL (Rabbit(Female, Male), Dermal, 90 d): > 150 mg/kg Dermal Experimental result, Key study NOAEL (Rat(Female), Oral, 90 d): < 82 mg/kg Oral Experimental result, Key study NOAEL (Rat(Female), Inhalation, 2 yr): < 31 ppm(m) Inhalation Experimental result, Key study
Ethanol, 2-(2-butoxyethoxy)-	NOAEL (Rat(Female, Male), Oral, 90 d): 250 mg/kg Oral Experimental result, Key study NOAEL (Rat(Female, Male), Dermal, 13 Weeks): > 2,000 mg/kg Dermal Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation, 90 - 120 d): 14 ppm(m) Inhalation Experimental result, Key study
Morpholine	NOAEL (Rat(Female, Male), Inhalation): 36 ppm(m) Inhalation Experimental result, Key study LOAEL (Rat(Female), Oral, 56 d): 500 mg/kg Oral Experimental result, Key study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Benzene, methyl-	in vivo (Rabbit): Irritating Experimental result, Key study
2-Propanone	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Ethanol, 2-butoxy-	in vivo (Rabbit): Irritating Experimental result, Key study
Ethanol, 2-(2-butoxyethoxy)-	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Morpholine	in vivo (Rabbit): Corrosive Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):



Benzene, methyl-	Rabbit, 24 - 72 hrs: Not irritating
2-Propanone	Irritating. Rabbit, 24 hrs: Minimum grade of severe eye irritant
Ethanol, 2-butoxy-	Rabbit, 24 - 72 hrs: Irritating
Ethanol, 2-(2-butoxyethoxy)-	Rabbit, 24 - 72 hrs: Highly irritating
Sodium hydroxide (Na(OH))	Corrosive Rabbit, 2 d: 10% Sodium Hydroxide- Category 1; 0.5% Sodium Hydroxide- Slightly irritating to eyes

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

Benzene, methyl-	Skin sensitization:, in vivo (Guinea pig): Non sensitising
2-Propanone	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Ethanol, 2-butoxy-	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Ethanol, 2-(2-butoxyethoxy)-	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Morpholine	Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specified substance(s):

Benzene, methyl- Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specified substance(s):



Benzene, methyl-
2-Propanone

Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.
Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Specified substance(s):
Benzene, methyl- Category 2

Aspiration Hazard

Product: No data available.

Specified substance(s):
Benzene, methyl- May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):
Benzene, methyl- LC 50 (Oncorhynchus kisutch, 96 h): 5.5 mg/l Experimental result, Key study
2-Propanone LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key study
Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Butane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Ethanol, 2-butoxy- LC 50 (Oncorhynchus mykiss, 96 h): 1,474 mg/l Experimental result, Key study
Ethanol, 2-(2-butoxyethoxy)- LC 50 (Lepomis macrochirus, 96 h): 1,300 mg/l Experimental result, Key study
LC 50 (Pimephales promelas, 96 h): 2,400 mg/l Experimental result, Supporting study
Sodium hydroxide (Na(OH)) LC 50 (Western mosquitofish (Gambusia affinis), 96 h): 125 mg/l Mortality
LC 50 (Gambusia affinis, 96 h): < 180 mg/l Experimental result, Supporting study
Morpholine LC 50 (Oncorhynchus mykiss, 96 h): 180 mg/l Experimental result, Key study



Aquatic Invertebrates

Product:	No data available.
Specified substance(s):	
Benzene, methyl-	LC 50 (Water flea (Daphnia magna), 48 h): 54.6 - 174.7 mg/l Mortality LC 50 (Ceriodaphnia dubia, 2 d): 3.78 mg/l Experimental result, Key study
2-Propanone	LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study
Butane	LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study
Ethanol, 2-butoxy-	EC 50 (Daphnia magna, 48 h): 1,550 mg/l Experimental result, Key study
Ethanol, 2-(2-butoxyethoxy)-	LC 50 (Daphnia magna, 48 h): +/- 1,743 mg/l QSAR QSAR, Supporting study
Sodium hydroxide (Na(OH))	EC 50 (Water flea (Ceriodaphnia dubia), 48 h): 34.59 - 47.13 mg/l Intoxication
Morpholine	EC 50 (Daphnia magna, 48 h): 45 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product:	No data available.
Specified substance(s):	
Benzene, methyl-	NOAEL (Oncorhynchus kisutch): 1.39 mg/l Experimental result, Key study LOAEL (Oncorhynchus kisutch): 2.77 mg/l Experimental result, Key study
Ethanol, 2-butoxy-	NOAEL (Danio rerio): > 100 mg/l Experimental result, Key study

Aquatic Invertebrates

Product:	No data available.
Specified substance(s):	
Benzene, methyl-	LOAEL (Ceriodaphnia dubia): 2.76 mg/l Experimental result, Key study NOAEL (Ceriodaphnia dubia): 0.74 mg/l Experimental result, Key study
2-Propanone	LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study
Ethanol, 2-butoxy-	EC 50 (Daphnia magna): 297 mg/l Experimental result, Key study EC 10 (Daphnia magna): 134 mg/l Experimental result, Key study
Morpholine	EC 50 (Daphnia magna): 12 mg/l Experimental result, Key study NOAEL (Daphnia magna): 5 mg/l Experimental result, Key study

Toxicity to Aquatic Plants

Product:	No data available.
-----------------	--------------------

Persistence and Degradability

Biodegradation

Product:	No data available.
-----------------	--------------------



Specified substance(s):

Benzene, methyl-	100 % (14 d) Detected in water. Experimental result, Weight of Evidence study 86 % Detected in water. Experimental result, Weight of Evidence study
2-Propanone	90.9 % (28 d) Detected in water. Experimental result, Key study
Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
Butane	100 % (385.5 h) Detected in water. Experimental result, Key study
Ethanol, 2-butoxy-	90.4 % Detected in water. Experimental result, Key study
Ethanol, 2-(2-butoxyethoxy)-	85 % (28 d) Detected in water. Experimental result, Key study
Morpholine	> 90 % (24 h) Sediment Experimental result, Key study 80 - 94 % (24 h) Sediment Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Benzene, methyl-	Leuciscus idus, Bioconcentration Factor (BCF): 90 Aquatic sediment Experimental result, Key study
2-Propanone	Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment Experimental result, Not specified
Morpholine	Cyprinus carpio, Bioconcentration Factor (BCF): < 2.8 Aquatic sediment Experimental result, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Benzene, methyl-	No data available.
2-Propanone	No data available.
Propane	No data available.
Butane	No data available.
Ethanol, 2-butoxy-	No data available.
Ethanol, 2-(2-butoxyethoxy)-	No data available.



Quaternary ammonium compounds,
benzyl(hydrogenated tallow alkyl)dimethyl,
bis(hydrogenated tallow alkyl)dimethylammonium salt with b
Sodium hydroxide (Na(OH))
Morpholine

No data available.
No data available.
No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number: UN 1950
UN Proper Shipping Name: Aerosols, flammable
Transport Hazard Class(es)
Class: 2.1
Label(s): –
Packing Group: II
Marine Pollutant: No

Environmental Hazards: No
Marine Pollutant: No

Special precautions for user: Not regulated.

IMDG

UN Number: UN 1950
UN Proper Shipping Name: Aerosols, flammable
Transport Hazard Class(es)
Class: 2
Label(s): –
EmS No.: –
Packing Group: –

Environmental Hazards: No
Marine Pollutant: No

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950
Proper Shipping Name: Aerosols, flammable
Transport Hazard Class(es):
Class: 2.1



Label(s): –
Packing Group: –
Environmental Hazards: No
Marine Pollutant: No
Special precautions for user: Not regulated.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Quartz (SiO ₂)	lung effects immune system effects Cancer kidney effects

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Benzene, methyl-	lbs. 1000
2-Propanone	lbs. 5000
Propane	lbs. 100
Butane	lbs. 100
Sodium hydroxide (Na(OH))	lbs. 1000
Morpholine	lbs. 100
1,2-Ethanediamine	lbs. 5000
Morpholine, 4-ethyl-	lbs. 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

- Fire Hazard
- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard
- Flammable aerosol
- Skin Corrosion/Irritation
- Serious Eye Damage/Eye Irritation
- Toxic to reproduction
- Aspiration Hazard

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
2-Propanone		
1,2-Ethanediamine	lbs. 5000	lbs. 10000

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
--------------------------	----------------------------



Benzene, methyl-	lbs. 1000
2-Propanone	lbs. 5000
Propane	lbs. 100
Butane	lbs. 100
Ethanol, 2-butoxy-	
Ethanol, 2-(2-butoxyethoxy)-	
Sodium hydroxide (Na(OH))	lbs. 1000
Morpholine	lbs. 100
Ethanol, 2-methoxy-	
1,2-Ethanediamine	lbs. 5000
Morpholine, 4-ethyl-	lbs. 100

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
1,2-Ethanediamine	lbs
Benzene, methyl-	10000 lbs
2-Propanone	10000 lbs
Propane	10000 lbs
Butane	10000 lbs
Ethanol, 2-butoxy-	10000 lbs
Ethanol, 2-(2-butoxyethoxy)-	10000 lbs
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, bis(hydrogenated tallow alkyl)dimethylammonium salt with b	10000 lbs
Sodium hydroxide (Na(OH))	10000 lbs
Morpholine	10000 lbs
Quartz (SiO2)	10000 lbs
Ethanol, 2-methoxy-	10000 lbs
Morpholine, 4-ethyl-	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>	<u>Reporting threshold for other users</u>	<u>Reporting threshold for manufacturing and processing</u>
Benzene, methyl-	lbs	lbs.
Ethanol, 2-butoxy-	N230 lbs	N230 lbs.
Ethanol, 2-(2-butoxyethoxy)-	N230 lbs	N230 lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Benzene, methyl-	Developmental toxin. 03 2008
Quartz (SiO2)	Carcinogenic. 05 2011



Ethanol, 2-methoxy- Developmental toxin. 03 2008
Ethanol, 2-methoxy- Male reproductive toxin. 03 2008

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Benzene, methyl-
2-Propanone
Propane
Butane
Ethanol, 2-butoxy-
Ethanol, 2-(2-butoxyethoxy)-

US. Massachusetts RTK - Substance List

Chemical Identity

Quartz (SiO₂)
1,2-Ethanediamine

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Benzene, methyl-
2-Propanone
Propane
Butane
Ethanol, 2-butoxy-
Ethanol, 2-(2-butoxyethoxy)-
9-Octadecenoic acid (9Z)-

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

Inventory Status:

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.
Japan (ENCS) List:	Not in compliance with the inventory.



China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Korea Existing Chemicals Inv. (KECI):	Not in compliance with the inventory.
Canada NDSL Inventory:	Not in compliance with the inventory.
Philippines PICCS:	Not in compliance with the inventory.
US TSCA Inventory:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Mexico INSQ:	Not in compliance with the inventory.
Ontario Inventory:	On or in compliance with the inventory
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory

16. Other information, including date of preparation or last revision

Issue Date:	09/19/2019
Revision Information:	No data available.
Version #:	1.0
Further Information:	No data available.
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.