

SAFETY DATA SHEET

1. Identification

Product number 1000009125

Product identifier 15 OZ TERAND SOLVENT DEGREASER LB 12PK

Company information CPC

1000 INTEGRAM DRIVE

PACIFIC, MO 63069 United States General Assistance 800-327-1835

Company phone General Assistance 800-32
Emergency telephone US 1-866-836-8855

Emergency telephone outside

1-952-852-4646

US

Version # 01
Recommended use Cleaner
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSerious eye damage/eye irritationCategory 2ASensitization, skinCategory 1

Specific target organ toxicity, single exposure Category 3 narcotic effects

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May cause an allergic skin reaction. Causes serious eye irritation.

May cause drowsiness or dizziness.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection/face

protection. Wear protective gloves.

Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical

advice/attention. Wash contaminated clothing before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding $50^{\circ}\text{C}/122^{\circ}\text{F}$.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	60 - 80
Methyl Acetate		79-20-9	10 - 20
Carbon Dioxide		124-38-9	2.5 - 10
Xylene		1330-20-7	2.5 - 10
n-Heptane		142-82-5	1 - 2.5
d-Limonene		5989-27-5	0.1 - 1
Other components below reportable	e levels		2.5 - 10

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Eye contact

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Ingestion

Most important May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an symptoms/effects, acute and

allergic skin reaction. Dermatitis. Rash. delayed Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed. medical attention and special treatment needed

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire.

media

Specific hazards arising from Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. the chemical

Firefighters must use standard protective equipment including flame retardant coat, helmet with

Special protective equipment face shield, gloves, rubber boots, and in enclosed spaces, SCBA. and precautions for firefighters

Move containers from fire area if you can do so without risk. Containers should be cooled with Fire fighting water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose equipment/instructions

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Use standard firefighting procedures and consider the hazards of other involved materials. Move Specific methods

containers from fire area if you can do so without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

Value

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000			
Components	Туре		
Acetone (CAS 67-64-1)	PEL		

Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Carbon Dioxide (CAS	PEL	9000 mg/m3	
124-38-9)			
		5000 ppm	
Methyl Acetate (CAS 79-20-9)	PEL	610 mg/m3	
		200 ppm	
n-Heptane (CAS 142-82-5)	PEL	2000 mg/m3	
		500 ppm	
Xylene (CAS 1330-20-7)	PEL	435 mg/m3	
		100 ppm	
US. ACGIH Threshold Limit Values	•		
Components	Type	Value	
Components	Туре	value	
	STEL	500 ppm	
Acetone (CAS 67-64-1) Carbon Dioxide (CAS	STEL	500 ppm	
Acetone (CAS 67-64-1)	STEL TWA STEL	500 ppm 250 ppm 30000 ppm	
Acetone (CAS 67-64-1) Carbon Dioxide (CAS 124-38-9)	STEL TWA STEL TWA	500 ppm 250 ppm 30000 ppm 5000 ppm	
Acetone (CAS 67-64-1) Carbon Dioxide (CAS 124-38-9) Methyl Acetate (CAS	STEL TWA STEL	500 ppm 250 ppm 30000 ppm	
Acetone (CAS 67-64-1) Carbon Dioxide (CAS	STEL TWA STEL TWA	500 ppm 250 ppm 30000 ppm 5000 ppm	
Acetone (CAS 67-64-1) Carbon Dioxide (CAS 124-38-9) Methyl Acetate (CAS	STEL TWA STEL TWA STEL	500 ppm 250 ppm 30000 ppm 5000 ppm 250 ppm	
Acetone (CAS 67-64-1) Carbon Dioxide (CAS 124-38-9) Methyl Acetate (CAS 79-20-9)	STEL TWA STEL TWA STEL TWA	500 ppm 250 ppm 30000 ppm 5000 ppm 250 ppm	
Acetone (CAS 67-64-1) Carbon Dioxide (CAS 124-38-9) Methyl Acetate (CAS 79-20-9) n-Heptane (CAS 142-82-5)	STEL TWA STEL TWA STEL TWA STEL	500 ppm 250 ppm 30000 ppm 5000 ppm 250 ppm 200 ppm 500 ppm 400 ppm	
Acetone (CAS 67-64-1) Carbon Dioxide (CAS 124-38-9) Methyl Acetate (CAS 79-20-9)	STEL TWA STEL TWA STEL TWA STEL TWA STEL TWA	500 ppm 250 ppm 30000 ppm 5000 ppm 250 ppm 200 ppm 500 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards			
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	

Components	туре	value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Methyl Acetate (CAS 79-20-9)	STEL	760 mg/m3	
,		250 ppm	
	TWA	610 mg/m3	
		200 ppm	
n-Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3	
, ,	· ·	440 ppm	
	TWA	350 mg/m3	
		85 ppm	

Biological limit values

ACGIH Biological Exposure Indices				
Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Gas. Aerosol. **Form** Color Not available. Odor Not available. Not available. **Odor threshold** Not available. Ηq Melting point/freezing point Not available.

Initial boiling point and boiling

115.11 °F (46.17 °C) estimated

range

5.8 °F (-14.6 °C) estimated Flash point

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

2.6 % estimated

(%)

Flammability limit - upper

13.2 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 80 - 100 psig @70F estimated

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 844.05 °F (451.14 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Explosive properties Not explosive.

Heat of combustion (NFPA

30B)

24.75 kJ/g estimated

Oxidizing properties Not oxidizing.

Percent volatile 90.9 % estimated

Specific gravity 0.38 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoidAvoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong acids. Acids. Strong oxidizing agents. Nitrates. Aluminum. Halogens.

Hazardous decomposition No hazardous decomposition products are known.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Narcotic effects. May cause an allergic skin reaction.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal LD50	Guinea pig	> 7426 mg/kg, 24 Hours
LD30	Guinea pig	> 7420 mg/kg, 24 Hours
	Rabbit	-
	Rabbit	> 7426 mg/kg, 24 Hours
L.L. L.C.		> 9.4 ml/kg, 24 Hours
Inhalation LC50	Rat	55700 ppm, 3 Hours
2000	Nat	132 mg/l, 3 Hours
6 1		50.1 mg/l
Oral LD50	Rat	5800 mg/kg
LDSU	Rai	
		2.2 ml/kg
d-Limonene (CAS 5989-27-5)		
<u>Acute</u> Oral		
LD50	Rat	> 2000 mg/kg
Methyl Acetate (CAS 79-20-9)		3 3
Acute		
 Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC100	Rabbit	98.4 mg/l, 4 Hours
Oral		
LD50	Rat	6482 mg/kg
n-Heptane (CAS 142-82-5)		
<u>Acute</u>		
Dermal	Dahkit	2000 mm/km 24 Hours
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation LC50	Rat	> 29.29 mg/l, 4 Hours
	Rai	> 29.29 High, 4 Hours
Oral LD50	Rat	> 5000 mg/kg
Xylene (CAS 1330-20-7)	Nat	> 3000 mg/kg
Acute		
<u>Dermal</u>		
LD50	Rabbit	> 5000 ml/kg, 4 Hours
		12126 mg/kg, 24 Hours
Inhalation		5 6 .
LC50	Rat	5922 ppm, 4 Hours
Oral		
LD50	Mouse	5251 mg/kg
	Rat	3523 mg/kg
		10 ml/kg
		Č

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Not a respiratory sensitizer. Respiratory sensitization

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

d-Limonene (CAS 5989-27-5) 3 Not classifiable as to carcinogenicity to humans. Xylene (CAS 1330-20-7) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders in

laboratory animals.

Specific target organ toxicity single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects. **Chronic effects**

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
d-Limonene (CAS 5989-27-	-5)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia pulex)	69.6 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	0.619 - 0.796 mg/l, 96 hours
Methyl Acetate (CAS 79-20	-9)		
Aquatic			
Algae	IC50	Algae	120.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1026.7 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas)	295 - 348 mg/l, 96 hours
n-Heptane (CAS 142-82-5)			
Aquatic			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours
Xylene (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

^{*} Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

-0.24Acetone d-Limonene 4.232 Methyl Acetate 0.18

Partition coefficient n-octanol / water (log Kow)

n-Heptane 4.66 Xylene 3.12 - 3.2

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards No. ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant No. EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions
Transport in bulk according to
Annex II of MARPOL 73/78 and

LTD QTY
Not applicable.

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed. Xylene (CAS 1330-20-7) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

 Chemical name
 CAS number
 % by wt.

 Xylene
 1330-20-7
 2.5 - 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Acetone (CAS 67-64-1) Xylene (CAS 1330-20-7)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9) Methyl Acetate (CAS 79-20-9)

n-Heptane (CAS 142-82-5) Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

Methyl Acetate (CAS 79-20-9)

n-Heptane (CAS 142-82-5)

Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

Methyl Acetate (CAS 79-20-9)

n-Heptane (CAS 142-82-5)

Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Acetone (CAS 67-64-1)

Xylene (CAS 1330-20-7)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Acetaldehyde (CAS 75-07-0) Listed: April 1, 1988
Benzene (CAS 71-43-2) Listed: February 27, 1987
Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004

US - California Proposition 65 - CRT: Listed date/Developmental toxin

 Benzene (CAS 71-43-2)
 Listed: December 26, 1997

 Methanol (CAS 67-56-1)
 Listed: March 16, 2012

 Toluene (CAS 108-88-3)
 Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 07-19-2017

Version # 01

Disclaimer We cannot anticipate all conditions under which this information and its product, or the products of

other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written

based on the best knowledge and experience currently available.

Revision information Product and Company Identification: Alternate Trade Names

Product name: 15 OZ TERAND SOLVENT DEGREASER LB 12PK Product #: 1000009125 Version #: 01 Issue date: 07-19-2017 Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).