SAFETY DATA SHEET

1. Identification

Company phone

Product number 1000001330

Product identifier TERAND INDUSTRIAL SILICONE

Company information

1000 INTEGRAM DRIVE

PACIFIC, MO 63069 United States General Assistance 800-327-1835

1-866-836-8855 **Emergency telephone US Emergency telephone outside** 1-952-852-4646

US

01 Version #

Recommended use LUBRICANT **Recommended restrictions** None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 Skin corrosion/irritation Category 2 **Health hazards** Aspiration hazard Category 1

OSHA defined hazards Not classified.

Label elements



Signal word

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Wash thoroughly after handling. Wear protective gloves.

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash Response

with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated

clothing and wash before reuse.

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Storage Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal**

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment, Category 2

long-term hazard

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Propane		74-98-6	40 - 60
Naphtha, (Petroleum), Hydrotreated Light	1	64742-49-0	20 - 40

Product name: TERAND INDUSTRIAL SILICONE SDS US

Chemical name	Common name and synonyms	CAS number	%
n-Heptane		142-82-5	10 - 20
Methylcyclohexane		108-87-2	1 - 2.5
Other components below	reportable levels		2.5 - 10

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Move to fresh air. Call a physician if symptoms develop or persist. Inhalation

redness and pain.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Aspiration may cause pulmonary edema and pneumonitis. Dizziness. Skin irritation. May cause

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Product name: TERAND INDUSTRIAL SILICONE

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

V-1--

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1	Limits for Air	Contaminante	(20 CED 1010 1000)
US. USHA Table Z-1	LIMITS FOR AIR	Contaminants	(29 CFR 1910.1000)

Components	Туре	Value	
Methylcyclohexane (CAS 108-87-2)	PEL	2000 mg/m3	
		500 ppm	
n-Heptane (CAS 142-82-5)	PEL	2000 mg/m3	
		500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
,		1000 ppm	
US. ACGIH Threshold Limit Value	S		
Components	Туре	Value	
Methylcyclohexane (CAS 108-87-2)	TWA	400 ppm	
n-Heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
Methylcyclohexane (CAS 108-87-2)	TWA	1600 mg/m3	
		400 ppm	
n-Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3	
		440 ppm	
	TWA	350 mg/m3	
		85 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
(3.13.1.33.3)		1000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Face shield is recommended. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection For prolonged or repeated skin contact use suitable protective gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas. **Form** Aerosol. Color Not available. Not available. Odor Odor threshold Not available. Not available. Not available. Melting point/freezing point

Initial boiling point and boiling

range

-43.7 °F (-42.06 °C) estimated

Flash point -156.0 °F (-104.4 °C) PROPELLANT estimated

Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

1.3 % estimated

Flammability limit - upper

7.2 % estimated

(%)

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. Not available. Vapor pressure Not available. Vapor density Relative density Not available.

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **Viscosity**

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing. 0.63 estimated Specific gravity

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

Product name: TERAND INDUSTRIAL SILICONE Product #: 1000001330 Version #: 01 Issue date: 10-10-2018

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious Ingestion

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Dizziness. Skin irritation. May cause

redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways

Acute toxicity	May be fatal if swallowed and enters	airways.
Components	Species	Test Results
Methylcyclohexane (CAS 1	08-87-2)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
Vapor	B.11%	50.0
LC100	Rabbit	59.9 mg/l
LC50	Dog	> 4071 ppm, If <1L: Consumer Commodity Hours
		> 16.3 mg/l, If <1L: Consumer Commodity Hours
	Mouse	> 6564 ppm, If <1L: Consumer Commodity Hours
		> 26.3 mg/l, If <1L: Consumer Commodity Hours
	Rat	> 6564 ppm, If <1L: Consumer Commodity Hours
		> 26.3 mg/l, If <1L: Consumer Commodity Hours
LC50	Rat	16 mg/l, 4 Hours
Naphtha, (Petroleum), Hyd	rotreated Light (CAS 64742-49-0)	
Acute	,	
Dermal		
LD50	Guinea pig; Rabbit	> 9.4 ml/kg, 24 Hours
	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 5000 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours
		13700 ppm, 4 Hours
Oral		••
LD50	Rat	4820 mg/kg
n-Heptane (CAS 142-82-5)		• •
<u>Acute</u>		

Product name: TERAND INDUSTRIAL SILICONE

Rabbit

Dermal LD50

SDS US 5/10 Product #: 1000001330 Version #: 01 Issue date: 10-10-2018

> 2000 mg/kg, 24 Hours

Components	Species	Test Results
Inhalation		
LC50	Rat	> 29.29 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components		Species	Test Results	
Methylcyclohexane	(CAS 108-87-2)			
Aquatic				
Fish	LC50	Striped bass (Morone saxatilis)	5.8 mg/l, 96 hours	
n-Heptane (CAS 14	-2-82-5)			
Aquatic				
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours	

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Methylcyclohexane	3.61
n-Heptane	4.66
Propage	2 36

Product name: TERAND INDUSTRIAL SILICONE

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN1950 **UN number**

UN proper shipping name Transport hazard class(es) Aerosols, flammable, (each not exceeding 1 L capacity)

2.1 Class Subsidiary risk 2.1 Label(s)

Not applicable. Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

N82 Special provisions 306 Packaging exceptions Packaging non bulk None Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

IATA

UN number UN1950

UN proper shipping name

Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Not applicable. Packing group

Environmental hazards Yes **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

Packaging Exceptions LTD QTY

IMDG

UN number UN1950 **UN proper shipping name AEROSOLS**

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s)

Product name: TERAND INDUSTRIAL SILICONE

Product #: 1000001330 Version #: 01 Issue date: 10-10-2018

Packing group

Environmental hazards

Not applicable.

Marine pollutant

Yes

F-D, S-U **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions Transport in bulk according to Annex II of MARPOL 73/78 and LTD QTY Not applicable.

the IBC Code

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

SDS US Product #: 1000001330 Version #: 01 Issue date: 10-10-2018

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Naphtha, (Petroleum), Hydrotreated Light (CAS 64742-49-0)

US. Massachusetts RTK - Substance List

Methylcyclohexane (CAS 108-87-2)

n-Heptane (CAS 142-82-5) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Methylcyclohexane (CAS 108-87-2)

n-Heptane (CAS 142-82-5) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Methylcyclohexane (CAS 108-87-2)

n-Heptane (CAS 142-82-5) Propane (CAS 74-98-6)

US. Rhode Island RTK

Propane (CAS 74-98-6)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987 Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)

Toluene (CAS 108-88-3)

Listed: December 26, 1997

Listed: January 1, 1991

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Camorina i roposition de Citti Listed date/mais reproductive textil

Benzene (CAS 71-43-2) Listed: December 26, 1997

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Country(s) or region Inventory name On inventory (yes/no)*

Europe European Inventory of Existing Commercial Chemical

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) No
Japan Inventory of Existing and New Chemical Substances (ENCS) Yes

Korea Existing Chemicals List (ECL)

New Zealand

New Zealand Inventory

Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 10-10-2018

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names

Product name: TERAND INDUSTRIAL SILICONE SDS US