

Revision Date: 10/14/2019

SAFETY DATA SHEET

1. Identification

Product identifier: TERAND ADHESIVE SPRAY - 92012

Other means of identification

SDS number: RE1000011617

Recommended restrictions
Product Use: Adhesive

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: CPC

Address: 1000 INTEGRAM DRIVE

PACIFIC, MO 63069

Telephone: 1-800-327-1835

Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification Physical Hazards

Flammable aerosol

Category 1

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Toxic to reproduction Category 2
Specific Target Organ Toxicity - Category 3¹

Single Exposure

Specific Target Organ Toxicity - Category 2

Repeated Exposure

Aspiration Hazard Category 1

Target Organs

Narcotic effect.

Environmental Hazards

Acute hazards to the aquatic Category 2

environment

Chronic hazards to the aquatic Category 2

environment

Label Elements

Hazard Symbol:





Revision Date: 10/14/2019

Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Do

not breathe dust/fume/gas/mist/vapors/spray. Avoid release to the

environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific

treatment (see on this label). Take off contaminated clothing. Collect

spillage.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F. Store locked up. Store in a well-ventilated place. Keep

container tightly closed.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

2/17

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

| Chemical Identity | CAS number | Content in percent (%)* |
|---|-------------|-------------------------|
| 2-Propanone | 67-64-1 | 20 - <50% |
| Propane | 74-98-6 | 20 - <50% |
| Hexane | 110-54-3 | 10 - <20% |
| Naphtha (petroleum), hydrotreated light | 64742-49-0 | 10 - <25% |
| Maleic Anhydride Modified Liquid Polyisoprene | 841251-34-1 | 0.1 - <1% |
| Limestone | 1317-65-3 | 0.1 - <1% |
| Cyclohexane | 110-82-7 | 0.1 - <1% |
| Heptane | 142-82-5 | 0.1 - <1% |

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SDS US - RE1000002715



Revision Date: 10/14/2019

4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so

that stomach content doesn't get into the lungs.

Inhalation: Move to fresh air.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash contaminated clothing

before reuse. Get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do.

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.



Revision Date: 10/14/2019

Methods and material for containment and cleaning up:

Absorb spill with vermiculite or other inert material, then place in a container

for chemical waste.

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Stop

the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you

can do so without risk.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling: Avoid contact with eyes. Wash hands thoroughly after handling. Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities:

Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after

use. Aerosol Level 1

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| Chemical Identity | Туре | Exposure Limit Values | Source |
|--|------|-----------------------|---|
| 2-Propanone | STEL | 1,000 ppm 2,400 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| • | PEL | 1,000 ppm 2,400 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | TWA | 250 ppm | US. ACGIH Threshold Limit Values (03 2015) |
| | TWA | 750 ppm 1,800 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | STEL | 500 ppm | US. ACGIH Threshold Limit Values (03 2015) |
| | REL | 250 ppm 590 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| Propane | REL | 1,000 ppm 1,800 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | PEL | 1,000 ppm 1,800 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | TWA | 1,000 ppm 1,800 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| Hexane | TWA | 50 ppm 180 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | PEL | 500 ppm 1,800 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | REL | 50 ppm 180 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | TWA | 50 ppm | US. ACGIH Threshold Limit Values (2008) |
| Naphtha (petroleum), hydrotreated light | PEL | 100 ppm 400 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016) |
| | REL | 100 ppm 400 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2010) |
| | TWA | 100 ppm 400 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| Limestone - Total | REL | 10 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| Limestone - Respirable. | REL | 5 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| Limestone - Respirable fraction. | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Limestone - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | TWA | 15 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| Limestone - Respirable fraction. | TWA | 5 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| Cyclohexane | TWA | 100 ppm | US. ACGIH Threshold Limit Values (2008) |
| | TWA | 300 ppm 1,050 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |



Revision Date: 10/14/2019

| | REL | 300 ppm | 1,050 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
|---|--------------|----------------|--|--|
| | PEL | 300 ppm | 1,050 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Heptane | TWA | 400 ppm | 1,600 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | REL | 85 ppm | 350 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | PEL | | 2,000 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | STEL | 500 ppm | 2,000 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 400 ppm | | US. ACGIH Threshold Limit Values (02 2012) |
| | STEL | 500 ppm | | US. ACGIH Threshold Limit Values (02 2012) |
| | Ceil_Time | 440 ppm | _ | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| Talc (Mg3H2(SiO3)4) - Respirable fraction. | TWA | | 2 mg/m3 | US. ACGIH Threshold Limit Values (2008) |
| Talc (Mg3H2(SiO3)4) - Respirable. | REL | | 2 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| Talc (Mg3H2(SiO3)4) - Respirable dust. | TWA | | 2 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| Talc (Mg3H2(SiO3)4) | TWA | | 20 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Talc (Mg3H2(SiO3)4) - Respirable. | TWA | | 2.4 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| | TWA | | 0.1 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Benzene, methyl- | STEL | 150 ppm | 560 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | REL | 100 ppm | 375 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | TWA | 100 ppm | 375 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | Ceiling | 300 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | TWA | 20 ppm | | US. ACGIH Threshold Limit Values (2008) |
| | TWA | 200 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | MAX. CONC | 500 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | STEL | 150 ppm | 560 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| Phenol | TWA REL | 5 ppm 5 ppm | 19 mg/m3 | US. ACGIH Threshold Limit Values (2008) US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | Ceil_Time | 15.6 ppm | 60 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | PEL | 5 ppm | 19 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | TWA | 5 ppm | 19 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| Benzene, ethyl- | STEL | 125 ppm | 545 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | REL | 100 ppm | 435 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | PEL | 100 ppm | 435 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | STEL | 125 ppm | 545 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 100 ppm | 435 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 20 ppm | | US. ACGIH Threshold Limit Values (12 2010) |
| Benzene | REL | 0.1 ppm | | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | TWA | 1 ppm | | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | Ceiling | 25 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | TWA | 0.5 ppm | | US. ACGIH Threshold Limit Values (2008) |
| | STEL | 2.5 ppm | | US. ACGIH Threshold Limit Values (2008) |
| | STEL | 5 ppm | | US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006) |
| | OSHA_AC T | 0.5 ppm | | US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006) |
| | TWA | 10 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | MAX. CONC | 50 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | STEL | 5 ppm | | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 1 ppm | | US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006) |



Revision Date: 10/14/2019

| | STEL | 1 ppm | | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
|-------------------|--------------|---------|-----------|--|
| Naphthalene | PEL | 10 ppm | 50 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| | TWA | 10 ppm | 50 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 10 ppm | | US. ACGIH Threshold Limit Values (2008) |
| | STEL | 15 ppm | 75 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | REL | 10 ppm | 50 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | STEL | 15 ppm | 75 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| Benzene, ethenyl- | TWA | 20 ppm | | US. ACGIH Threshold Limit Values (2008) |
| | STEL | 40 ppm | | US. ACGIH Threshold Limit Values (2008) |
| | REL | 50 ppm | 215 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | STEL | 100 ppm | 425 mg/m3 | US. NIOSH: Pocket Guide to Chemical Hazards (2005) |
| | TWA | 50 ppm | 215 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | STEL | 100 ppm | 425 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| | TWA | 100 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | Ceiling | 200 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | MAX. CONC | 600 ppm | | US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006) |
| | TWA | 2 ppm | | US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values (03 2018) |

Biological Limit Values

| Chemical Identity | Exposure Limit Values | Source |
|---|--------------------------------|---------------------|
| 2-Propanone (acetone: Sampling time: End of shift.) | 25 mg/l (Urine) | ACGIH BEL (03 2015) |
| Hexane (2,5-Hexanedion, without hydrolysis: Sampling time: End of shift.) | 0.5 mg/l (Urine) | ACGIH BEL (03 2018) |
| Benzene, methyl- (toluene: Sampling time: End of shift.) | 0.03 mg/l (Urine) | ACGIH BEL (03 2013) |
| Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.) | 0.3 mg/g (Creatinine in urine) | ACGIH BEL (03 2013) |
| Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.) | 0.02 mg/l (Blood) | ACGIH BEL (03 2013) |
| Phenol (Phenol with hydrolysis: Sampling time: End of shift.) | 250 mg/g (Creatinine in urine) | ACGIH BEL (03 2013) |
| Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.) | 0.15 g/g (Creatinine in urine) | ACGIH BEL (02 2014) |
| Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.) | 25 μg/g (Creatinine in urine) | ACGIH BEL (03 2013) |
| Benzene (t,t-Muconic acid: Sampling time: End of shift.) | 500 μg/g (Creatinine in urine) | ACGIH BEL (03 2013) |
| Benzene, ethenyl- (Mandelic acid plus phenylglyoxylic acid: Sampling time: End of shift.) | 400 mg/g (Creatinine in urine) | ACGIH BEL (03 2013) |
| Benzene, ethenyl- (styrene: Sampling time: End of shift.) | 40 μg/l (Urine) | ACGIH BEL (03 2015) |

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If exposure limits have not been established, maintain airborne levels

to an acceptable level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Other: Wear suitable protective clothing. Wear chemical-resistant gloves, footwear,

and protective clothing appropriate for the risk of exposure. Contact health

and safety professional or manufacturer for specific information.



Revision Date: 10/14/2019

7/17

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Avoid contact with eyes. When

using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands

before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: Spray Aerosol
Color: No data available.
Odor: No data available.
Odor threshold: No data available.
pH: No data available.
Melting point/freezing point: No data available.
Initial boiling point and boiling range: No data available.

Flash Point: -104.44 °C

Evaporation rate:No data available. **Flammability (solid, gas):**No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): Estimated 10.2 %(V)
Flammability limit - lower (%): Estimated 2.5 %(V)
Explosive limit - upper (%): No data available.
Explosive limit - lower (%): No data available.

Vapor pressure: 3,585.2738 - 4,964.2253 hPa (20 °C)

Vapor density:No data available.Density:No data available.Relative density:No data available.

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
No data available.
Partition coefficient (n-octanol/water):
No data available.
No data available.
Decomposition temperature:
No data available.
Viscosity:
No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

SDS_US - RE1000002715



Revision Date: 10/14/2019

Hazardous Decomposition

Products:

No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

No data available. Ingestion:

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

2-Propanone LD 50 (Rat): 5,800 mg/kg

Hexane LD 50: > 2,000 mg/kg

Naphtha (petroleum),

hydrotreated light

LD 50 (Rat): > 5,000 mg/kg

Maleic Anhydride Modified Liquid Polyisoprene

LD 50: > 2,000 mg/kg

Limestone LD 50: > 2,000 mg/kg

Cyclohexane LD 50 (Rat): > 5,000 mg/kg

Heptane LD 50 (Rat): > 5,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

LD 50 (Rabbit): > 3,750 mg/kg

Specified substance(s):

2-Propanone LD 50 (Rabbit): > 7,426 mg/kg

Hexane LD 50 (Rabbit): > 2,000 mg/kg

Naphtha (petroleum),

hydrotreated light



Revision Date: 10/14/2019

Maleic Anhydride **Modified Liquid** Polyisoprene

LD 50: > 2,000 mg/kg

Limestone

LD 50: > 2,000 mg/kg

Cyclohexane

LD 50 (Rabbit): > 2,000 mg/kg

Heptane

Product:

LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

Not classified for acute toxicity based on available data.

Specified substance(s):

2-Propanone

LC 50 (Rat): 50.1 mg/l

LC 50: > 5 mg/l

Propane

LC 50: > 100 mg/l LC 50: > 100 mg/l

Hexane

LC 50 (Rat): > 31.86 mg/l

LC 50: > 5 mg/l

Naphtha (petroleum), LOAEL (Human): 2,400 mg/m3 hydrotreated light

LC 50 (Rat): > 7,630 mg/m3

LC 50: > 5 mg/l

Maleic Anhydride Modified Liquid

LC 50: > 5 mg/l

Polyisoprene

Cyclohexane

LC 50: > 20 mg/l

Limestone

LC 50: > 5 mg/lLC 50: > 20 mg/l

LC 50 (Rat): > 32,880 mg/m3

Heptane

LC 50 (Rat): > 29.29 mg/l

Repeated dose toxicity

Product:

No data available.

Specified substance(s):

2-Propanone

NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental

result, Key study

Propane

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

Hexane

NOAEL (Mouse(Male), Inhalation, 13 Weeks): 500 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Mouse(Male), Inhalation, 13 Weeks): 1,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Male), Inhalation, 16 Weeks): 3,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Mouse(Female), Inhalation, 13 Weeks): 500 ppm(m) Inhalation

Experimental result, Key study

Naphtha (petroleum), hydrotreated light

LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg Oral Readacross based on grouping of substances (category approach), Key study

NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal

Experimental result, Supporting study

NOAEL (Rat(Female, Male), Inhalation): 10,000 mg/m3 Inhalation



Revision Date: 10/14/2019

Experimental result, Key study

Cyclohexane NOAEL (Rat(Female, Male), Inhalation, 13 - 18 Weeks): 7,000 ppm(m)

Inhalation Experimental result, Key study

NOAEL (Mouse(Female, Male), Inhalation, 13 - 18 Weeks): 500 ppm(m)

Inhalation Experimental result, Key study

Heptane NOAEL (Rat(Male), Inhalation): 12,470 mg/m3 Inhalation Experimental

result, Key study

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

2-Propanone in vivo (Rabbit): Not irritant Experimental result, Supporting study

Cyclohexane Review (Various): Irritating.

in vivo (Rabbit): Not irritant Experimental result, Weight of Evidence study

Heptane in vivo (Rabbit): Irritating Read-across based on grouping of substances

(category approach), Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

2-Propanone Irritating.

Rabbit, 24 hrs: Minimum grade of severe eye irritant

Hexane Rabbit, 1 - 72 hrs: Not irritating

Naphtha (petroleum), hydrotreated light

Rabbit, 24 - 72 hrs: Not irritating

Heptane Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product: No data available.

Specified substance(s):

2-Propanone Skin sensitization:, in vivo (Guinea pig): Non sensitising Naphtha (petroleum), Skin sensitization:, in vivo (Guinea pig): Non sensitising

hydrotreated light

Cyclohexane Skin sensitization:, in vivo (Guinea pig): Non sensitising Heptane Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.



Revision Date: 10/14/2019

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specified substance(s):

Suspected of damaging fertility or the unborn child. Hexane

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specified substance(s):

2-Propanone Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects. Hexane Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects. Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects. Cyclohexane

Heptane Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Specified substance(s):

Hexane Inhalation - vapor: Nervous System - Category 2

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product: No data available.

Specified substance(s):

Hexane May be fatal if swallowed and enters airways.

Naphtha (petroleum),

May be fatal if swallowed and enters airways.

hydrotreated light Cyclohexane

May be fatal if swallowed and enters airways. Heptane May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

2-Propanone LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key

study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Hexane LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2.101 - 2.981 mg/l

Mortality

Naphtha (petroleum),

hydrotreated light

LC 50 (96 h): 8.41 mg/l Experimental result, Key study

Cyclohexane LC 50 (Pimephales promelas, 96 h): 4.53 mg/l Experimental result, Key

study

Heptane LC 50 (Mozambique tilapia (Tilapia mossambica), 96 h): 375 mg/l Mortality

SDS US - RE1000002715



Revision Date: 10/14/2019

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

2-Propanone LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study

Hexane EC 50 (Daphnia magna, 48 h): 21.85 mg/l QSAR QSAR, Key study

LC 50 (Water flea (Daphnia magna), 24 h): > 50 mg/l Mortality

Naphtha (petroleum), hydrotreated light

EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study

Cyclohexane EC 50 (Daphnia magna, 48 h): 0.9 mg/l Experimental result, Key study

Heptane EC 50 (Daphnia magna, 48 h): 1.5 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish

Product: NOEC : Estimated < 1 mg/l

Aquatic Invertebrates

Product:

No data available.

Specified substance(s):

2-Propanone LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study

Hexane NOAEL (Daphnia magna): 4.888 mg/l QSAR QSAR, Key study

Naphtha (petroleum), hydrotreated light

EC 50 (Daphnia magna): 10 mg/l Experimental result, Key study NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study

Heptane NOAEL (Daphnia magna): 0.17 mg/l Read-across based on grouping of

substances (category approach), Key study

EC 50 (Daphnia magna): 0.23 mg/l Read-across based on grouping of

substances (category approach), Key study

Toxicity to Aquatic Plants

Product:

No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

2-Propanone 90.9 % (28 d) Detected in water. Experimental result, Key study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Hexane 81 % Detected in water. Read-across based on grouping of substances

(category approach), Key study

Naphtha (petroleum), hydrotreated light

90.35 % (28 d) Detected in water. Experimental result, Supporting study

Cyclohexane 77 % (28 d) Detected in water. Experimental result, Key study

Heptane 70 % Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential



Revision Date: 10/14/2019

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

2-Propanone Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment

Experimental result, Not specified

Hexane Pimephales promelas, Bioconcentration Factor (BCF): 501.19 Aquatic

sediment QSAR, Key study

Naphtha (petroleum), Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by

hydrotreated light calculation, Key study

Cyclohexane Cyprinus carpio, Bioconcentration Factor (BCF): 37 - 129 Aquatic sediment

Experimental result, Supporting study

Heptane Bioconcentration Factor (BCF): 552 Aquatic sediment Estimated by

calculation, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Naphtha (petroleum), hydrotreated light Log Kow: > 2.4 - < 5.7 23 °C Yes Experimental result, Key study Log Kow: 2.2 - 5.2 23 °C Yes Experimental result, Key study Log Kow: 2.2 - 6.1 23 °C Yes Experimental result, Key study

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

No data available. 2-Propanone Propane No data available. Hexane No data available. Naphtha (petroleum), hydrotreated light No data available. Maleic Anhydride Modified Liquid Polyisoprene No data available. Limestone No data available. Cyclohexane No data available. Heptane No data available.

Other adverse effects: Toxic to aquatic life with long lasting effects.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1
Label(s): Packing Group: II
Marine Pollutant: No
Environmental Hazards: No
Marine Pollutant No

Special precautions for user: Not regulated.



Revision Date: 10/14/2019

IMDG

UN Number: UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2 Label(s): –

EmS No.: F-D, S-U

Packing Group: -

Environmental Hazards: Yes Marine Pollutant No

Special precautions for user: Not regulated.

IATA

UN Number: UN 1950

Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es):

Class: 2.1
Label(s): Packing Group: -

Environmental Hazards: Yes Marine Pollutant No

Special precautions for user: Not regulated. Cargo aircraft only: Allowed.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Chemical Identity OSHA hazard(s)

Benzene Flammability
Cancer
Aspiration
Eye

Blood Skin

respiratory tract irritation Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

| Chemical Identity | Reportable quantity |
|--------------------------|---------------------|
| 2-Propanone | lbs. 5000 |
| Propane | lbs. 100 |
| Methane, 1,1'-oxybis- | lbs. 100 |
| Hexane | lbs. 5000 |
| Cyclopentane, methyl- | lbs. 100 |
| Cyclohexane | lbs. 1000 |
| Heptane | lbs. 100 |
| Benzene, methyl- | lbs. 1000 |
| Phenol | lbs. 1000 |
| Benzene, ethyl- | lbs. 1000 |
| Benzene | lbs. 10 |



Revision Date: 10/14/2019

Naphthalene lbs. 100 Benzene, ethenyl- lbs. 1000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

Flammable aerosol Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Toxic to reproduction

Specific Target Organ Toxicity - Single Exposure Specific Target Organ Toxicity - Repeated Exposure

Aspiration Hazard

SARA 302 Extremely Hazardous Substance

| Chemical Identity | <u>quantity</u> | Threshold Planning Quantity |
|-------------------|-----------------|-----------------------------|
| 2-Propanone | | |
| Hexane | | |
| Phenol | lbs. 1000 | |

SARA 304 Emergency Release Notification

| SARA 304 Emergency Release Notification | |
|---|---------------------|
| Chemical Identity | Reportable quantity |
| 2-Propanone | lbs. 5000 |
| Propane | lbs. 100 |
| Methane, 1,1'-oxybis- | lbs. 100 |
| Hexane | lbs. 5000 |
| Cyclopentane, methyl- | lbs. 100 |
| Cyclohexane | lbs. 1000 |
| Heptane | lbs. 100 |
| Benzene, methyl- | lbs. 1000 |
| Phenol | lbs. 1000 |
| Benzene, ethyl- | lbs. 1000 |
| Benzene | lbs. 10 |
| Naphthalene | lbs. 100 |
| Benzene, ethenyl- | lbs. 1000 |
| | |

SARA 311/312 Hazardous Chemical

| Chemical Identity | Threshold Planning Quantity |
|---|------------------------------------|
| Phenol | lbs |
| 2-Propanone | 10000 lbs |
| Propane | 10000 lbs |
| Hexane | 10000 lbs |
| Naphtha (petroleum), hydrotreated light | 10000 lbs |
| Maleic Anhydride Modified Liquid Polyisoprene | 10000 lbs |
| Limestone | 10000 lbs |
| Cyclohexane | 10000 lbs |
| Heptane | 10000 lbs |
| Talc (Mg3H2(SiO3)4) | 10000 lbs |
| Benzene, methyl- | 10000 lbs |
| Benzene, ethyl- | 10000 lbs |
| Benzene | 10000 lbs |
| Naphthalene | 10000 lbs |
| Benzene, ethenyl- | 10000 lbs |



Revision Date: 10/14/2019

SARA 313 (TRI Reporting)

Reporting Reporting threshold for manufacturing and

<u>Chemical Identity</u> <u>other users</u> <u>processing</u>

Hexane lbs lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Hexane Male reproductive toxin. 12 2017
Benzene, methyl- Developmental toxin. 03 2008

Benzene, ethyl- Carcinogenic. 05 2011

Benzene Developmental toxin. 03 2008

Benzene Carcinogenic. 05 2011

Benzene Male reproductive toxin. 03 2008

Naphthalene Carcinogenic. 05 2011 Benzene, ethenyl- Carcinogenic. 04 2016

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

2-Propanone

Propane

Methane, 1,1'-oxybis-

Hexane

Naphtha (petroleum), hydrotreated light

Cyclopentane, methyl-

US. Massachusetts RTK - Substance List

Chemical Identity

Phenol Benzene

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

2-Propanone

Propane

Methane, 1,1'-oxybis-

Hexane

Naphtha (petroleum), hydrotreated light

Cyclopentane, methyl-

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

2-Propanone Hexane

Stockholm convention

2-Propanone

Hexane

Rotterdam convention

2-Propanone

Hexane

SDS US - RE1000002715



Revision Date: 10/14/2019

Kyoto protocol

Inventory Status:

Australia AICS: Not in compliance with the inventory.

EINECS, ELINCS or NLP: Not in compliance with the inventory.

Japan (ENCS) List: Not in compliance with the inventory.

China Inv. Existing Chemical Substances: Not in compliance with the inventory.

Korea Existing Chemicals Inv. (KECI): Not in compliance with the inventory.

Canada NDSL Inventory: Not in compliance with the inventory.

Philippines PICCS: Not in compliance with the inventory.

New Zealand Inventory of Chemicals: Not in compliance with the inventory.

Japan ISHL Listing: Not in compliance with the inventory.

Japan Pharmacopoeia Listing: Not in compliance with the inventory.

Mexico INSQ: Not in compliance with the inventory.

Ontario Inventory: Not in compliance with the inventory.

Taiwan Chemical Substance Inventory: Not in compliance with the inventory.

Canada DSL Inventory List: On or in compliance with the inventory

US TSCA Inventory:

On or in compliance with the inventory

16.Other information, including date of preparation or last revision

Issue Date: 10/14/2019

Revision Information: No data available.

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.